

TOR-1N

Future Ready Dual Flow Channel Data Logger



DUAL FLOW CHANNEL DATA LOGGER USED FOR MONITORING, RECORDING AND TRANSMITTING THROUGH NB-IOT, LTE-M OR 2G (SMS/GPRS)

Applications

- + Leak Detection
- + Flow Monitoring
- + Network Modelling
- + Commercial Logging

Specifications

Power

2x Lithium battery (7.2V, 13Ah)
>5 years life under typical usage
External battery (optional)

Memory

16MB Non-volatile
320,000 records
Cyclic or Stop when full

Inputs

up to 2 x Pulse/Events
1 x Event Input

Connectors

2 x Souriau

Modem

NB-IoT/LTE-M with 2G fallback
Low Power

Communications

SMS/Data to server
Remote firmware upgrades and configuration
Internal antenna
SMA external antenna connection
USB to serial configuration

Alarms

Multiple High/Low
Fastline and human readable SMS
10 Profile alarms

Clock

Auto correction on server connection

Schedules

1 second to 24 hour logging intervals
Configurable transmission schedules

Environmental

IP68 -20°C to 70°C

Weight

750g

Software

TOR Configuration Software
AquaGuard - Online Portal

TOR-1N Future Ready Dual Flow Channel Data Logger

Options/Ordering codes

			A		B
	TOR-1N	-	X	-	X
No Modem NB-IoT/ LTE-M Internal Antenna			L NBE		
Examples					
TOR-1N-L	No Modem, 3 Digital				
TOR-1N-NBE	NB-IoT/ LTE-M Modem, Internal Antenna, 3 Digital				

Accessories

Part Number	Description
ACC-COMM-003	USB Communication Cable
ACC-CAB-006	4 Pin Souriau Flying Input Lead - 1.5m
BATT-LD6	114Ah External Battery Pack
ACC-PRT-036	Wall Mounting Bracket
ACC-PRT-045	Meter Pit Hanging Bracket
ACC-ANT-009	External Antenna 0.5m cable
ACC-PRT-012	External Antenna Mounting Bracket

Dimensions (mm)

