

TOR-2N

Future Ready Single Channel Pressure Data Logger



SINGLE CHANNEL PRESSURE DATA LOGGER FOR MONITORING, RECORDING AND TRANSMITTING THROUGH NB-IOT, LTE-M OR 2G (SMS/GPRS)

Applications

- + Pressure Monitoring
- + Network Modelling
- + PRV Monitoring
- + Critical Point Monitoring

Specifications

Power

2 x Lithium battery (7.2V, 13Ah)
>5 years life under typical usage
External battery (optional)

Memory

16MB Non-volatile
320,000 records
Cyclic or Stop when full

Inputs

1 Swiss Made internal pressure transducer (0.25/0.1%)

Connectors

1 x Souriau
1 x Standard Quickfit Male Port

Modem

NB-IoT/LTE-M with 2G fallback
Low Power

Communications

SMS/Data to server
Remote firmware upgrades and configuration
Internal antenna
SMA external antenna connection
USB to serial configuration

Alarms

Multiple High/Low
Fastlane and human readable SMS
10 Profile alarms

Clock

Auto correction on server connection

Schedules

1 second to 24 hour logging intervals
Configurable transmission schedules

Environmental

IP68 -20°C to 70°C

Weight

750g

Software

TOR Configuration Software
AquaGuard - Online Portal

Future Ready Single Channel Pressure Data Logger

Options/Ordering codes

			A		B
	TOR-2N	-	X	-	X
No Modem NB-IoT/ LTE-M Internal Antenna			L NBE		
5 Bar					A
10 Bar					B
20 Bar					C
Examples					
TOR-2N-L-A	No Modem, 1 Pressure (10 Bar)				
TOR-2N-NBE-B	NB-IoT/ LTE-M Modem, Internal Antenna, 1 Pressure (10 Bar)				

Accessories

Part Number	Description
ACC-COMM-003	USB Communication Cable
BATT-LD6	114Ah External Battery Pack
ACC-PRT-036	Wall Mounting Bracket
ACC-PRT-045	Meter Pit Hanging Bracket
ACC-ANT-009	External Antenna 0.5m cable
ACC-PRT-012	External Antenna Mounting Bracket
ACC-PRES-000	Curly/ Flexible Pressure Hose – 1.5m
ACC-PRES-003	1/8" Male BSP to Female Quick-fit Adapter

Dimensions (mm)

